

Desktop Soldering Robot

QUICK ET9594FYA



Feature

X/Y Rail

Double-rail for X/Y axis, precise moving.

Y Motor

Closed loop control, no out-of-step, precise speed control

Heating Controller

High frequency current heating, fast heating and thermal recovery, intelligent temperature compensation

Alarm Functions

Temperature abnormal and solder wire lack alarm available.

Communication Ports

DB37, DB9

Protocol

RS485, RS422, RS232

Efficiency improvement

Shuttle Y, robot soldering when products are being loaded and unloaded, time saving.

Specifications:

Model	QUICK ET9594FYA-A	
Axis	4	
Power Consumption	600W	
Power of Heating Controller	200W	
Moving Range	X/Y	500mm/400mm
	Z	100mm
	X/Y	0.1~800 mm/sec
Speed Range	Z	0.1~300 mm/sec
	R	±180°
	Repeatability	X/Y/Z
Machine Load	Z	3kg
	Platform	8kg
Effective Range(Soldering Area)	200*400mm(Shuttle Y)	
Overall Dimension(W*D*H)	845x679x899mm	
Weight	90kg	

Accessories



9036 Tip Calibration Device



Fume Extractor



9039 N2 Generator



371T Series Wire Feeding & Cutting Device

Overall Dimension

